

MAC 15~36KTL3-XL

- 3 MPPTs
- 220V Three Phase Solution
- Smart diagnosis
- High efficiency up to 98.8%
- Local WiFi configuration
- OLED display and touch button
- AC&DC type II SPD



P O W E R
- I N G O
T O M O -
R R O W O



Datasheet	MAC 15KTL3-XL	MAC 20KTL3-XL	MAC 22KTL3-XL	MAC 25KTL3-XL	MAC 30KTL3-XL	MAC 36KTL3-XL
Input Data(DC)						
Max. recommended PV power (for module STC)	22500W	30000W	33000W	37500W	45000W	54000W
Max.DC voltage	1100V					
Start voltage	250V					
Nominal voltage	360V					
MPPT voltage range	200V-1000V					
No. of MPP trackers	3					
No. of PV strings per MPP tracker	4/4/4					
Max. input current per MPP tracker	52A/52A/52A					
Max. short-circuit current per MPP tracker	55A/55A/55A					
Output Data(AC)						
Rated AC output power	15000W	20000W	22000W	25000W	30000W	36000W
Max. AC apparent power	16600VA@220VAC	22200VA@220VAC	24400VA@220VAC	27800VA@220VAC	33300VA@220VAC	36000VA@220VAC 39200VA@240VAC
Nominal AC voltage(range*)	127V/220V(101.6-139.7V)					
AC grid frequency(range*)	50/60 Hz(46~54/56~64Hz)					
Nominal AC output current	39.4A	52.5A	57.7A	65.6A	78.8A	94.5A
Max. output current	43.6A	58.3A	64.0A	73.0A	87.4A	94.5A
Power factor(@nominal power)	>0.99					
Adjustable power factor	0.8leading ...0.8lagging					
THDi	<3%					
AC grid connection type	3W+N+PE					
Efficiency						
Max. efficiency	98.8%					
European efficiency	98.5%					
MPPT efficiency	99.9%					
Protection Devices						
DC reverse polarity protection	Yes					
DC switch	Yes					
AC/DC surge protection	Type II / Type II					
Insulation resistance monitoring	Yes					
AC short-circuit protection	Yes					
Ground fault monitoring	Yes					
Grid monitoring	Yes					
Anti-islanding protection	Yes					
Residual-current monitoring unit	Yes					
General Data						
Dimensions(W / H / D)	680/508/281mm					
Weight	52kg					
Operating temperature range	- 25°C ... +60°C					
Nighttime power consumption	< 1W					
Topology	Transformerless					
Cooling	Smart air cooling					
Protection degree	IP65					
Relative humidity	0~100%					
Altitude	4000m					
DC connection	H4/MC4(Optional)					
AC connection	Cable gland+OT terminal					
Display	OLED+LED/WIFI+APP					
Interfaces: RS485 / USB /WIFI/ GPRS / RF	Yes/Yes /Optional/Optional/Optional					
Warranty: 5 years / 10 years	Yes/Optional					
EN 61000-3/6, EN/IEC 62109-1, EN/IEC 62109-2, IEC 60068, IEC61683, IEC62116, IEC 61727,UL1741,IEEE1547						

* The AC voltage range and frequency range may vary depending on specific country grid standard.
All specifications are subject to change without notice.